



Product name

Tie and connecting rod joint puller with hydraulic lift cylinder








Used for hydraulic extraction of ball pins when dismantling ball joints on push and tie rods.

Art. No. 129-5-50-H20

Series 129-5-50-H

EAN 4021176000324



| | Technical attribute | Metric | Imperial |
|---|----------------------|--|--|
|  | Fork opening | 50 - 55 mm | 2 - 2 3/16 inch |
|  | Opening range | 120 mm | 4 3/4 inch |
|  DIN ISO 7803 | For ball-joint sizes | 50 - 60 mm | |
|  | Application | Speziell / special: Liebherr LTC, LTM | Speziell / special: Liebherr LTC, LTM |
| max. | Maximum pressure | 450 bar | 450 bar |
| max. | Maximum load | 20 t | 22 US t |
|  | Weight | 9.2 kg | |
|  | Mouth height min. | 7 - 28,5 mm | 1/4 - 1 1/8 inch |
|  | Mouth height max. | mm | inch |



has to be accomplished with



Hydraulic hand pump

YHP-325

Technologies



HYDRAULIC

Pullers with hydraulic function.



Spare part

| Art. No. | Product name |
|-----------------|---------------------|
| YSM-200 | Lift cylinder |
| 1294531 | Clamping lever |
| 129456L | Mechanical screw |
| 1294557 | Bolt |
| 1294526L | Screw |
| 129-5-45-ERS | Spare part |
| 1295014 | Frame |