



Product name

## Universal 2-jaw puller with extremely narrow jaws

For removing gears, bearings, sprockets, synchronizer bodies, etc., in tight or difficult-to-access spaces.

Art. No. 20-1-S-T  
 Series 20-S-T  
 EAN 4021176321641



	Technical attribute	Metric	Imperial
	Spread	30 - 90 mm	1 3/16 - 3 1/2 inch
	Depth	100 mm	3 7/8 inch
	Spread used internal	70 - 140 mm	2 3/4 - 5 1/2 inch
	Hexagon drive (male)	17 mm	
	Maximum load	2,5 t	2.5 US t
	Maximum torque	35 Nm	25.5 ft lb
	Weight	1.18 kg	
	Space below	3 mm	1/8 inch
	Space next to it	12 mm	1/2 inch
	Number of jaws	2	2



## Technologies



### GLIDE & FIX

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.



### ARMLOCK

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.



### SWITCH

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



## Spare part

<b>Art. No.</b>	<b>Product name</b>
614160	Mechanical pressure spindle.
1-94-P	2 extremely narrow jaws (pair)
20-1-T	2-jaw cross bar

## Accessories

<b>Art. No.</b>	<b>Product name</b>
219-1	Clamp for 2-jaw pullers
1-194-P	2 extremely narrow jaws (pair)
1-254-P	2 extremely narrow jaws (pair)
1-94-E	Jaws (individual)
K-600-014	Set of interchangeable pressure pads for KUKKO pressure screws