



Product name

Universal 2-jaw puller wheel extremely narrow, quick adjusting jaws

For removing gears, bearings, sprockets, synchronizer bodies, etc., in tight or difficult-to-access spaces.

Art. No. 20-10+S-T

Series 20+S-T

EAN 4021176321368



	Technical attribute	Metric	Imperial
	Spread	30 - 120 mm	1 3/16 - 4 3/4 inch
	Depth	100 mm	3 7/8 inch
	Spread used internal	70 - 180 mm	2 3/4 - 7 1/8 inch
	Hexagon drive (male)	17 mm	
	Maximum load	2,5 t	2.5 US t
	Maximum torque	35 Nm	25.5 ft lb
	Weight	1.35 kg	
	Space below	3 mm	1/8 inch
	Space next to it	12 mm	1/2 inch
	Number of jaws	2	2




Technologies



GLIDE & FIX

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.



ARMLOCK

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.



QUICK ADJUST

The knurls allow the jaws to be quickly released and moved on the cross-beam without the need for tools.



SWITCH

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



Spare part

Art. No.	Product name
614160	Mechanical pressure spindle.
1-95-P	2 extremely narrow, quick adjusting jaws (pair)
1-195-P	2 extremely narrow, quick adjusting jaws (pair)
1-255-P	2 extremely narrow, quick adjusting jaws (pair)
20-10-T	2-jaw cross bar

Accessories

Art. No.	Product name
219-1	Clamp for 2-jaw pullers
1-195-P	2 extremely narrow, quick adjusting jaws (pair)
1-255-P	2 extremely narrow, quick adjusting jaws (pair)
K-600-014	Set of interchangeable pressure pads for KUKKO pressure screws



Part of

Art. No.

Product name

K-2030-10+S-T

Universal 2-jaw and 3-jaw puller set with narrow, quick-adjusting pulling jaws

Also included in

Art. No.

Product name

K-2030-10+S-T

Universal 2-jaw and 3-jaw puller set with narrow, quick-adjusting pulling jaws