



Product name \*

# Universal 2-jaw puller with extended jaws

For removing bearings, gears, discs, etc.

Art. No. 20-2-3

Series 20

EAN 4021176466564



	Technical attribute	Metric	Imperial
ф	Spread	40 - 160 mm	1 5/8 - 6 3/8 inch
Ţ	Depth	300 mm	11 7/8 inch
$\Box$	Spread used internal	100 - 220 mm	3 7/8 - 8 5/8 inch
	Hexagon drive (male)	22 mm	
max.	Maximum torque	150 Nm	
max.	Maximum load	6,0 t	6.5 US t
$\nabla$	Weight	4.38 kg	
± <b>*</b>	Space below	9 mm	3/8 inch
*   t-	Space next to it	40 mm	1 5/8 inch
×	Number of jaws	2	2



## **Technologies**



#### **SWITCH**

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



#### **GLIDE & FIX**

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.



#### **ARMLOCK**

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.

20-2-3 Product data sheet www.kukko.com



# Spare part

Art. No.	Product name
621220	Mechanical pressure spindle.
2-300-P	2 extended jaws (pair)
20-2-T	2-jaw cross bar

### Accessories

Art. No.	Product name
8-01	Long hydraulic spindle
2-150-P	2 pulling jaws (pair)
2-V-150-P	2 jaw extensions (pair)
30-2-T	3-jaw cross bar
K-600-025	Set of interchangeable pressure pads for KUKKO pressure screws
2-300-E	Jaw with extension (indiv.)

**20-2-3** Product data sheet www.kukko.com



# Can be used alternatively with

Art. No.	Product name
2-151-P	2 narrow jaws (pair)
2-301-P	2 narrow jaws (pair)
2-152-P	2 quick adjusting jaws (pair)
2-302-P	2 quick adjusting jaws (pair)
2-153-P	2 narrow, quick adjusting jaws (pair)
2-303-P	2 narrow, quick adjusting jaws (pair)

## Also included in

Art. No.	Product name
K-20-15	Universal puller set with separator

**20-2-3** Product data sheet www.kukko.com