



Product name *

Universal 2-jaw puller with narrow jaws

For removing bearings, gears, discs, etc. for tight or difficult-to-access spaces.

Art. No. 20-2-S

Series 20-S

EAN 4021176727368



	Technical attribute	Metric	Imperial
	Spread	40 - 160 mm	1 5/8 - 6 3/8 inch
	Depth	150 mm	5 7/8 inch
	Spread used internal	100 - 220 mm	3 7/8 - 8 5/8 inch
	Hexagon drive (male)	22 mm	
max.	Maximum load	5 t	5.5 US t
max.	Maximum torque	120 Nm	88.5 ft lb
	Weight	3.005 kg	
	Space below	4 mm	3/16 inch
	Space next to it	19 mm	3/4 inch
	Number of jaws	2	2



Technologies



GLIDE & FIX

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.



ARMLOCK

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.



SWITCH

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



Spare part

Art. No.	Product name
621220	Mechanical pressure spindle.
2-151-P	2 narrow jaws (pair)
20-2-T	2-jaw cross bar

Accessories

Art. No.	Product name
8-01	Long hydraulic spindle
2-301-P	2 narrow jaws (pair)
2-V-150-P	2 jaw extensions (pair)
2-151-P	2 narrow jaws (pair)
30-2-T	3-jaw cross bar
K-600-025	Set of interchangeable pressure pads for KUKKO pressure screws
2-151-E	Jaws (individual)



Can be used alternatively with

Art. No.	Product name
2-150-P	2 pulling jaws (pair)
2-300-P	2 extended jaws (pair)
2-152-P	2 quick adjusting jaws (pair)
2-302-P	2 quick adjusting jaws (pair)
2-153-P	2 narrow, quick adjusting jaws (pair)
2-303-P	2 narrow, quick adjusting jaws (pair)

Part of

Art. No.	Product name
20-ST-S	Sales display for 2-jaw puller with narrow jaws

Spare part of

Art. No.	Product name
20-ST-S	Sales display for 2-jaw puller with narrow jaws