



Product name

# Universal 2-jaw puller with quick adjusting jaws

For removing bearings, gears, discs, etc.

Art. No. 20-2+C

Series 20+C

EAN 4021176039737



	Technical attribute	Metric	Imperial
Ü	Spread	40 - 160 mm	1 5/8 - 6 3/8 inch
Ţ	Depth	150 mm	5 7/8 inch
Щ	Spread used internal	100 - 220 mm	3 7/8 - 8 5/8 inch
	Hexagon drive (male)	22 mm	
max.	Maximum load	6,0 t	6.5 US t
max.	Maximum torque	150 Nm	110.5 ft lb
Δ, Ω	Weight	3.08 kg	
± <b>•</b>	Space below	9 mm	3/8 inch
*   <del>  -</del>	Space next to it	40 mm	1 5/8 inch
×	Number of jaws	2	2

20-2+C Product data sheet www.kukko.com



# **Technologies**



#### **GLIDE & FIX**

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.



## **ARMLOCK**

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.



## **QUICK ADJUST**

The knurls allow the jaws to be quickly released and moved on the cross-beam without the need for tools.



## **SWITCH**

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



# Part of

Art. No.	Product name
20-ST+C	Sales display for 2-jaw pullers
WT-100+C	Puller product range - exterior pulling - BASIC+

**20-2+C** Product data sheet www.kukko.com