



Product name \*

## Universal 2-jaw puller with extended jaws

For removing bearings, gears, discs, etc.

Art. No. 20-3-4

Series 20

EAN 4021176467066



	Technical attribute	Metric	Imperial
	Spread	65 - 250 mm	2 5/8 - 9 7/8 inch
	Depth	400 mm	15 3/4 inch
	Spread used internal	180 - 340 mm	7 1/8 - 13 3/8 inch
	Hexagon drive (male)	27 mm	
	Maximum torque	300 Nm	
	Maximum load	8,5 t	9 US t
	Weight	9.075 kg	
	Space below	20 mm	3/4 inch
	Space next to it	67 mm	2 5/8 inch
	Number of jaws	2	2



## Technologies



### SWITCH

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



### GLIDE & FIX

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.



### ARMLOCK

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.



## Spare part

<b>Art. No.</b>	<b>Product name</b>
626300	Mechanical pressure spindle.
3-400-P	2 extended jaws (pair)
20-3-T	2-jaw cross bar

## Accessories

<b>Art. No.</b>	<b>Product name</b>
8-02	Long hydraulic spindle
9-1	Auxiliary hydraulic ram
9-2	Auxiliary hydraulic ram
9-3	Auxiliary hydraulic ram
3-200-P	2 pulling jaws (pair)
3-300-P	2 extended jaws (pair)
3-500-P	2 extended jaws (pair)
3-250-P	2 pulling jaws (pair)
30-3-T	3-jaw cross bar
K-600-025	Set of interchangeable pressure pads for KUKKO pressure screws
3-400-E	Jaw with extension (indiv.)



## Can be used alternatively with

<b>Art. No.</b>	<b>Product name</b>
3-201-P	2 narrow jaws (pair)
3-301-P	2 narrow jaws (pair)
3-401-P	2 narrow jaws (pair)
3-501-P	2 narrow jaws (pair)
3-202-P	2 quick adjusting jaws (pair)
3-302-P	2 quick adjusting jaws (pair)
3-402-P	2 quick adjusting jaws (pair)
3-502-P	2 quick adjusting jaws (pair)
3-203-P	2 narrow, quick adjusting jaws (pair)
3-303-P	2 narrow, quick adjusting jaws (pair)
3-403-P	2 narrow, quick adjusting jaws (pair)
3-503-P	2 narrow, quick adjusting jaws (pair)