



Product name *

Universal 2-jaw puller with narrow jaws

For removing bearings, gears, discs, etc. for tight or difficult-to-access spaces.

Art. No. 20-3-S

Series 20-S

EAN 4021176727511



	Technical attribute	Metric	Imperial
Ü	Spread	65 - 250 mm	2 5/8 - 9 7/8 inch
	Depth	200 mm	7 7/8 inch
ÜΠ	Spread used internal	180 - 340 mm	7 1/8 - 13 3/8 inch
	Hexagon drive (male)	27 mm	
max.	Maximum load	9 t	9.5 US t
max.	Maximum torque	250 Nm	184 ft lb
Δ'Δ	Weight	6.81 kg	
± •	Space below	6,5 mm	1/4 inch
* +	Space next to it	52 mm	2 1/16 inch
J×	Number of jaws	2	2



Technologies



GLIDE & FIX

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.



ARMLOCK

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.



SWITCH

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



Spare part

Art. No.	Product name
626300	Mechanical pressure spindle.
3-201-P	2 narrow jaws (pair)
20-3-T	2-jaw cross bar

Accessories

Art. No.	Product name
3-301-P	2 narrow jaws (pair)
3-401-P	2 narrow jaws (pair)
3-501-P	2 narrow jaws (pair)
K-600-025	Set of interchangeable pressure pads for KUKKO pressure screws
3-201-E	Jaws (individual)

Part of

Art. No.	Product name
20-ST-S	Sales display for 2-jaw puller with narrow jaws

20-3-S Product data sheet www.kukko.com



Spare part of

Art. No.	Product name
20-ST-S	Sales display for 2-jaw puller with narrow jaws

20-3-S Product data sheet www.kukko.com