



Product name \*


## Universal 2-jaw puller with narrow jaws

For removing bearings, gears, discs, etc. for tight or difficult-to-access spaces.

Art. No. 20-30-S

Series 20-S

EAN 4021176727696



	Technical attribute	Metric	Imperial
	Spread	65 - 350 mm	2 5/8 - 13 3/4 inch
	Depth	200 mm	7 7/8 inch
	Spread used internal	180 - 440 mm	7 1/8 - 17 3/8 inch
	Hexagon drive (male)	27 mm	
	Maximum load	9 t	9.5 US t
	Maximum torque	250 Nm	184 ft lb
	Weight	7.38 kg	
	Space below	6,5 mm	1/4 inch
	Space next to it	52 mm	2 1/16 inch
	Number of jaws	2	2



## Technologies



### GLIDE & FIX

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.



### ARMLOCK

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.



### SWITCH

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



## Spare part

<b>Art. No.</b>	<b>Product name</b>
626300	Mechanical pressure spindle.
3-201-P	2 narrow jaws (pair)
20-30-T	2-jaw cross bar

## Accessories

<b>Art. No.</b>	<b>Product name</b>
3-301-P	2 narrow jaws (pair)
3-401-P	2 narrow jaws (pair)
3-501-P	2 narrow jaws (pair)
K-600-025	Set of interchangeable pressure pads for KUKKO pressure screws