



Product name *

2-jaw puller with swiveling jaws

For removing bearings, gears, discs, etc.

 Art. No.
 208-02

 Series
 208

 EAN
 4021176432651



| | Technical attribute | Metric | Imperial |
|-------------------|---------------------------|--------------|--------------------|
| \Box | Spread | 20 - 230 mm | 3/4 - 9 1/16 inch |
| | Depth | 150 - 190 mm | 5 7/8 - 7 1/2 inch |
| } ≭ | Number of possible depths | 2 | 2 |
| | Hexagon drive (male) | 22 mm | |
| max. | Maximum load | 2,5 t | 2.5 US t |
| max. | Maximum torque | 50 Nm | 6.5 ft lb |
| $\Delta^{}\Delta$ | Weight | 2.49 kg | |
| ± | Space below | 13 mm | 1/2 inch |
| | Space next to it | 30 mm | 1 3/16 inch |
| × | Number of jaws | 2 | 2 |

KUKKO // Pull forward



Technologies



SWITCH

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



Spare part

| Art. No. | Product name |
|--------------|------------------------------|
| 621220 | Mechanical pressure spindle. |
| 201-2-T | Cross-beam |
| 208-02-190-P | 2 pulling jaws (pair) |

Accessories

| Art. No. | Product name |
|-----------|--|
| K-600-025 | Set of interchangeable pressure pads for KUKKO pressure screws |