



Product name

# Universal 3-jaw puller with extremely narrow, quick adjusting jaws

For removing gears, bearings, sprockets, synchronizer bodies, etc., in tight or difficult-to-access spaces.

Art. No. 30-10+S-T

Series 30+S-T

EAN 4021176321337



	Technical attribute	Metric	Imperial
Ü	Spread	27 - 130 mm	1 1/16 - 5 1/8 inch
Ţ	Depth	100 mm	3 7/8 inch
Ħ	Spread used internal	70 - 180 mm	2 3/4 - 7 1/8 inch
	Hexagon drive (male)	17 mm	
max.	Maximum load	3 t	3 US t
max.	Maximum torque	40 Nm	29.5 ft lb
Δ, Ω	Weight	1.535 kg	
± <b>•</b>	Space below	3 mm	1/8 inch
*   <del>  -</del>	Space next to it	12 mm	1/2 inch
×	Number of jaws	3	3



## **Technologies**



#### **GLIDE & FIX**

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.



#### **ARMLOCK**

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.



#### **QUICK ADJUST**

The knurls allow the jaws to be quickly released and moved on the cross-beam without the need for tools.



#### **SWITCH**

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



# Spare part

Art. No.	Product name
614135	Mechanical pressure spindle.
1-95-S	3 extremely narrow, quick adjusting jaws (set)
1-195-S	3 extremely narrow, quick adjusting jaws (set)
30-10-T	Cross-beam

### Accessories

Art. No.	Product name
1-95-S	3 extremely narrow, quick adjusting jaws (set)
1-195-S	3 extremely narrow, quick adjusting jaws (set)
1-255-S	3 extremely narrow, quick adjusting jaws (set)
K-600-014	Set of interchangeable pressure pads for KUKKO pressure screws

## Also included in

Art. No.	Product name
K-2030-10+S-T	Universal 2-jaw and 3-jaw puller set with narrow, quick-adjusting pulling jaws