



Product name \*

## Universal 3-jaw puller with extremely narrow, quick adjusting jaws

For removing gears, bearings, sprockets, synchronizer bodies, etc., in tight or difficult-to-access spaces.

Art. No. 30-1+S-T

Series 30+S-T

EAN 4021176321320



	Technical attribute	Metric	Imperial
	Spread	27 - 90 mm	1 1/16 - 3 1/2 inch
	Depth	100 mm	3 7/8 inch
	Spread used internal	70 - 140 mm	2 3/4 - 5 1/2 inch
	Hexagon drive (male)	17 mm	
max.	Maximum load	3 t	3 US t
	Maximum torque	40 Nm	29.5 ft lb
	Weight	1.345 kg	
	Space below	3 mm	1/8 inch
	Space next to it	12 mm	1/2 inch
J <sub>x</sub>	Number of jaws	3	3



## Technologies



### GLIDE & FIX

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.



### ARMLOCK

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.



### QUICK ADJUST

The knurls allow the jaws to be quickly released and moved on the cross-beam without the need for tools.



### SWITCH

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



## Spare part

<b>Art. No.</b>	<b>Product name</b>
614135	Mechanical pressure spindle.
1-95-S	3 extremely narrow, quick adjusting jaws (set)
1-195-S	3 extremely narrow, quick adjusting jaws (set)
30-1-T	3-jaw cross bar

## Accessories

<b>Art. No.</b>	<b>Product name</b>
1-95-S	3 extremely narrow, quick adjusting jaws (set)
1-195-S	3 extremely narrow, quick adjusting jaws (set)
1-255-S	3 extremely narrow, quick adjusting jaws (set)
K-600-014	Set of interchangeable pressure pads for KUKKO pressure screws