




Product name

Universal 3-jaw puller

For removing bearings, gears, discs, etc.





	Technical attribute	Metric	Imperial
$\mathbf{\Box}$	Spread	35 - 200 mm	1 3/8 - 7 7/8 inch
	Depth	150 mm	5 7/8 inch
μ	Spread used internal	100 - 260 mm	3 7/8 - 10 1/4 inch
	Hexagon drive (male)	22 mm	
max.	Maximum load	7 t	7.5 US t
max.	Maximum torque	150 Nm	110.5 ft lb
$\Delta^{\dagger}\Delta$	Weight	4.14 kg	
±	Space below	9 mm	3/8 inch
	Space next to it	40 mm	1 5/8 inch
×	Number of jaws	3	3



Technologies



SWITCH

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



GLIDE & FIX

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.



ARMLOCK

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.



Spare part

Art. No.	Product name
621220	Mechanical pressure spindle.
2-150-S	3 pulling arms (set)
30-20-T3	3-jaw cross bar

Accessories

Art. No.	Product name	
8-01	Long hydraulic spindle	
2-150-S	3 pulling arms (set)	
2-300-S	3 pulling arms (set)	
2-151-S	3 narrow jaws (set)	
2-301-S	3 narrow jaws (set)	
2-V-150-S	3 jaw extensions (set)	



Goes with

Art. No.	Product name
13-2	TRI-PULL with 3 segments

Also included in

Art. No.	Product name
WT-008	Puller product range - commercial vehicles - BASIC
30-20-T	Puller product range - industrial - BASIC
K-2030-20-B	Universal hydraulic 2-jaw and 3-jaw puller set
K-2030-20	Set of universal 2- and 3-jaw pullers