



Product name \*

## Universal 3-jaw puller with extended jaws

For removing bearings, gears, discs, etc.

Art. No. 30-3-25

Series 30

EAN 4021176901256



	Technical attribute	Metric	Imperial
	Spread	35 - 250 mm	1 3/8 - 9 7/8 inch
	Depth	250 mm	9 7/8 inch
	Spread used internal	180 - 340 mm	7 1/8 - 13 3/8 inch
	Hexagon drive (male)	27 mm	
	Maximum torque	250 Nm	
	Maximum load	10 t	11 US t
	Weight	10.195 kg	
	Space below	20 mm	3/4 inch
	Space next to it	67 mm	2 5/8 inch
	Number of jaws	3	3



## Technologies



### GLIDE & FIX

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.



### ARMLOCK

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.



### SWITCH

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



## Spare part

<b>Art. No.</b>	<b>Product name</b>
626300	Mechanical pressure spindle.
30-3-T	3-jaw cross bar
3-250-S	3 pulling arms (set)

## Accessories

<b>Art. No.</b>	<b>Product name</b>
9-1	Auxiliary hydraulic ram
9-2	Auxiliary hydraulic ram
9-3	Auxiliary hydraulic ram
K-600-025	Set of interchangeable pressure pads for KUKKO pressure screws