



Product name *

Universal 3-jaw puller-set

For removing bearings, gears, discs, etc.

Art. No. 30-3-P3

Series 30-P3

EAN 4021176111174



| | Technical attribute | Metric | Imperial |
|--|----------------------|----------------|----------------------------|
| | Spread | 250 mm | 9 7/8 inch |
| | Depth | 200/300/400 mm | 7 7/8; 11 7/8; 15 3/4 inch |
| | Spread used internal | 180 - 340 mm | 7 1/8 - 13 3/8 inch |
| | Hexagon drive (male) | 27 mm | |
| | Maximum torque | 250 Nm | |
| | Maximum load | 10 t | 11 US t |
| | Weight | 23.86 kg | |
| | Number of jaws | 3 | 3 |



Technologies



GLIDE & FIX

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.



ARMLOCK

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.



SWITCH

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



Spare part

| Art. No. | Product name |
|-----------------|------------------------------|
| 626300 | Mechanical pressure spindle. |
| 3-200-S | 3 pulling arms (set) |
| 3-300-S | 3 pulling arms (set) |
| 3-400-S | 3 pulling arms (set) |
| 30-3-T | 3-jaw cross bar |

Accessories

| Art. No. | Product name |
|-----------------|--|
| 9-1 | Auxiliary hydraulic ram |
| 9-2 | Auxiliary hydraulic ram |
| 9-3 | Auxiliary hydraulic ram |
| K-600-025 | Set of interchangeable pressure pads for KUKKO pressure screws |