



Product name \*

# Universal 3-jaw puller with quick adjusting jaws

For removing bearings, gears, discs, etc.

Art. No.	30-30+	
Series	30+	
EAN	4021176303333	

	Technical attribute	Metric	Imperial
$\Box$	Spread	50 - 375 mm	2 - 14 3/4 inch
	Depth	200 mm	7 7/8 inch
Ē	Spread used internal	180 - 440 mm	7 1/8 - 17 3/8 inch
	Hexagon drive (male)	36 mm	
max.	Maximum load	15 t	16 US t
max.	Maximum torque	250 Nm	184 ft lb
$\Delta^{\dot{-}}\Delta$	Weight	10.635 kg	
±	Space below	20 mm	3/4 inch
	Space next to it	67 mm	2 5/8 inch
×	Number of jaws	3	3



## Technologies



#### **GLIDE & FIX**

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.



#### ARMLOCK

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.



#### **QUICK ADJUST**

The knurls allow the jaws to be quickly released and moved on the cross-beam without the need for tools.



#### SWITCH

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



# Spare part

Art. No.	Product name
633400	Mechanical pressure spindle.
3-202-S	3 quick adjusting jaws (set)
11-0-T	Cross-beam
626300	Mechanical pressure spindle.

## Accessories

Art. No.	Product name
9-1	Auxiliary hydraulic ram
9-2	Auxiliary hydraulic ram
9-3	Auxiliary hydraulic ram
3-202-S	3 quick adjusting jaws (set)
3-302-S	3 quick adjusting jaws (set)
3-402-S	3 quick adjusting jaws (set)
K-600-025	Set of interchangeable pressure pads for KUKKO pressure screws