



Product name \*

## Universal 3-jaw puller

For removing bearings, gears, discs, etc.

Art. No. 30-30

Series 30

EAN 4021176303005



	Technical attribute	Metric	Imperial
	Spread	50 - 375 mm	2 - 14 3/4 inch
	Depth	200 mm	7 7/8 inch
	Spread used internal	180 - 440 mm	7 1/8 - 17 3/8 inch
	Hexagon drive (male)	36 mm	
	Maximum load	15 t	16 US t
	Maximum torque	250 Nm	184 ft lb
	Weight	10.5 kg	
	Space below	20 mm	3/4 inch
	Space next to it	67 mm	2 5/8 inch
	Number of jaws	3	3



## Technologies



### SWITCH

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



### GLIDE & FIX

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.



### ARMLOCK

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.



## Spare part

<b>Art. No.</b>	<b>Product name</b>
633400	Mechanical pressure spindle.
3-200-S	3 pulling arms (set)
11-0-T	Cross-beam
626300	Mechanical pressure spindle.

## Accessories

<b>Art. No.</b>	<b>Product name</b>
9-1	Auxiliary hydraulic ram
9-2	Auxiliary hydraulic ram
9-3	Auxiliary hydraulic ram
3-201-S	3 narrow jaws (set)
K-600-025	Set of interchangeable pressure pads for KUKKO pressure screws