



Product name *

Universal 3-jaw puller with narrow, quick adjusting jaws

For removing bearings, gears, discs, etc. for tight or difficult-to-access spaces.

Art. No. 30-3+S

Series 30+S

EAN 4021176757211



	Technical attribute	Metric	Imperial
Ü	Spread	46 - 250 mm	1 7/8 - 9 7/8 inch
Ţ	Depth	200 mm	7 7/8 inch
ÜΠ	Spread used internal	180 - 340 mm	7 1/8 - 13 3/8 inch
	Hexagon drive (male)	27 mm	
max.	Maximum load	13,5 t	14.5 US t
max.	Maximum torque	390 Nm	287 ft lb
Δ,Ω	Weight	9.3 kg	
± •	Space below	6,5 mm	1/4 inch
-1 I+-	Space next to it	52 mm	2 1/16 inch
×	Number of jaws	3	3



Technologies



GLIDE & FIX

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.



ARMLOCK

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.



QUICK ADJUST

The knurls allow the jaws to be quickly released and moved on the cross-beam without the need for tools.



SWITCH

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



Spare part

Art. No.	Product name
626300	Mechanical pressure spindle.
3-203-S	3 narrow, quick adjusting jaws (set)
30-3-T	3-jaw cross bar

Accessories

Art. No.	Product name
3-203-S	3 narrow, quick adjusting jaws (set)
3-303-S	3 narrow, quick adjusting jaws (set)
3-403-S	3 narrow, quick adjusting jaws (set)
3-503-S	3 narrow, quick adjusting jaws (set)
K-600-025	Set of interchangeable pressure pads for KUKKO pressure screws

Also included in

Art. No.	Product name
WT-010	Puller product range - commercial vehicles - TOP

30-3+S Product data sheet www.kukko.com