



Product name *

Universal 3-jaw puller

For removing bearings, gears, discs, etc.

 Art. No.
 30-5

 Series
 30

 EAN
 4021176303326



	Technical attribute	Metric	Imperial
ф	Spread	220 - 650 mm	8 5/8 - 25 5/8 inch
	Depth	300 - 500 mm	11 7/8 - 19 3/4 inch
μ	Spread used internal	290 - 740 mm	11 3/8 - 29 1/8 inch
	Hexagon drive (male)	41 mm	
max.	Maximum load	20 t	22 US t
max.	Maximum torque	650 Nm	479.5 ft lb
$\Delta^{\dagger}\Delta$	Weight	31.71 kg	
±	Space below	20 mm	3/4 inch
	Space next to it	67 mm	2 5/8 inch
×	Number of jaws	3	3



Technologies



GLIDE & FIX

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.



ARMLOCK

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.



SWITCH

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



Spare part

Art. No.	Product name
4-SP-S	3 Jaws with adjustable lengths (set)
11-650	Cross-beam for puller 11-2
637350	Mechanical pressure spindle.