



Product name

## Universal 2-jaw and 3-jaw puller set with narrow, quick-adjusting pulling jaws

For removing gears, bearings, sprockets, synchronizer bodies, etc., in tight or difficult-to-access spaces.

Art. No. K-2030-10+S-T

Series K-2030-10+S-T

EAN 4021176001710



	Technical attribute	Metric	Imperial
	Spread	120; 130 mm	4 3/4; 5 1/8 inch
	Depth	100 - 350 mm	3 7/8 - 13 3/4 inch
	Spread used internal	70 - 180 mm	2 3/4 - 7 1/8 inch
	Wrench size	17 mm	
	Maximum torque	35 Nm	
	Maximum load	2,5 t	2.5 US t
	Weight	8.91 kg	




## Technologies



### GLIDE & FIX

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.




### ARMLOCK

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.



### QUICK ADJUST

The knurls allow the jaws to be quickly released and moved on the cross-beam without the need for tools.



### SWITCH

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



## Accessories

<b>Art. No.</b>	<b>Product name</b>
K-600-014	Set of interchangeable pressure pads for KUKKO pressure screws

## Content

<b>Art. No.</b>	<b>Product name</b>
20-10+S-T	Universal 2-jaw puller wheel extremely narrow, quick adjusting jaws
30-10-T	Cross-beam
614250	Mechanical pressure spindle.
1-95-E	Jaws, individual
1-195-S	3 extremely narrow, quick adjusting jaws (set)
1-255-S	3 extremely narrow, quick adjusting jaws (set)