



Product name *

PULLPO" ball bearing puller set

To remove grooved ball bearings without causing damage and without having to dismantle the shaft.

Art. No.	K-70-A-C
Series	K-70-C
EAN	4021176021534



	Technical attribute	Metric	Imperial
	Ball bearing ISO	6000-6006; 6200-6205; 6300-6304	6000-6006; 6200-6205; 6300-6304
	Inner diameter of ball bearing	10 - 30 mm	3/8 - 1 3/16 inch
\bigcirc	Outer diameter of ball bearing	26 - 52 mm	1 1/32 - 2 1/16 inch
	Hexagon drive (male)	13 mm	
L	K-70 jaw length	70 mm	2 3/4 inch
×	Number of jaws	6	6
č	Number of rings	7 St. / pcs.	7 St. / pcs.
Ø	Diameter of support ring	19 - 38 mm	3/4 - 1 1/2 inch
× x	Counter-pressure pad for extraction of ball bearing with hollow shaft.	10 - 42 mm	3/8 - 1 5/8 inch
$\Delta^{\dagger}\Delta$	Weight	1.91 kg	

KUKKO // Pull forward



Technologies



PULLPO

The special cross-beam shape enables safe and easy mounting and automatic clamping of the jaws via leverage transmission. KUKKO // Pull forward



Spare part

Art. No.	Product name
700217	Large pressure pads