



Product name


PULLPO" ball bearing puller set











To remove grooved ball bearings without causing damage and without having to dismantle the shaft.

Art. No. K-70-C-C



Series K-70-C

EAN 4021176021565



	Technical attribute	Metric	Imperial
	Ball bearing ISO	6000-6020; 6200-6212; 6300-6311; 6403-6408	6000-6020; 6200-6212; 6300-6311; 6403-6408
	Inner diameter of ball bearing	10 - 100 mm	3/8 - 3 7/8 inch
	Outer diameter of ball bearing	26 - 150 mm	1 1/32 - 5 7/8 inch
	Hexagon drive (male)	13; 17 mm	
	K-70 jaw length	70; 156 mm	2 3/4; 6 3/16 inch
	Number of rings	13 St. / pcs.	13 St. / pcs.
	Number of jaws	14	14
	Diameter of support ring	19 - 77,5 mm	3/4 - 3 1/16 inch
	Counter-pressure pad for extraction of ball bearing with hollow shaft.	10 - 42 mm	3/8 - 1 5/8 inch
	Number of counter-pressure pads	4 St. / pcs.	4 St. / pcs.



	Technisches Attribut	Metric	Imperial
	Diameter of counter-pressure pads	35 - 80 mm	1 3/8 - 3 3/16 inch
	Weight	7.17 kg	



Technologies



PULLPO

The special cross-beam shape enables safe and easy mounting and automatic clamping of the jaws via leverage transmission.



Spare part

Art. No.

Product name

700217

Large pressure pads