




Product name

## Hydraulic push/pull device set

For separation and internal extraction of particularly large and tight bearings, gears, discs, etc. in industry and commercial vehicles.



Art. No. Y28-218  
 Series YX8-X18  
 EAN 4021176036651



	Technical attribute	Metric	Imperial
	Distance of side screw	135 - 300 mm	5 1/4 - 11 3/4 inch
	Depth of side screw	470 mm	18 1/2 inch
	Tension bolt depth with hydraulics below the cross-beam	300 mm	12 inch
	Diameter of the shaft	25 - 155 mm	1 - 6 1/8 inch
	Inner diameter of ball bearing	30 - 180 mm	
	Maximum load as pulling device only with tension bolts	15 t	16.5 US t
	Maximum load as pulling device with separator	15 t	16.5 US t
	Maximum load as pulling device with internal extractor	10 t	11.0 US t
max.	Maximum pressure	394 bar	394 bar
	Weight	60 kg	



## Technologies



### HYDRAULIC

Pullers with hydraulic function.



## Content

<b>Art. No.</b>	<b>Product name</b>
Y-221-E	Internal extractors
YHP-325	Hydraulic hand pump
Y-215-3	Separator for hydraulic push/pull device
YDB-27E	Pressure pad for hollow rams
YRH-202	Hydraulic hollow ram
Y20-180	Push/pulling device (without hydraulic hollow ram for pump drive)
Y218-06-P	240 mm tension bolts, pair
Y218-08-P	570 mm tension bolts, pair
Y218-31-P	Pair of connectors for tension bolts
Y218-33	Quick-adjust nuts
Y218-10	Crank
Y218-11	Mechanical screw