



Product name

## Hydraulic push/pulling device with hydraulic hollow ram for pump drive

For removing particularly large and tight bearings, gears, discs, etc. using separator blades and internal extractors.

Art. No. Y38-180

Series Y-180

EAN 4021176037498



	Technical attribute	Metric	Imperial
	Distance of side screw	180 - 420 mm	7 1/8 - 16 1/2 inch
	Depth of side screw	520 mm	20 1/2 inch
	Tension bolt depth with hydraulics below the cross-beam	330 mm	13 inch
	Maximum load as pulling device only with tension bolts	25 t	27.5 US t
max.	Maximum pressure	514 bar	514 bar
	Weight	37.68 kg	



## Technologies



### HYDRAULIC

Pullers with hydraulic function.



## Spare part

<b>Art. No.</b>	<b>Product name</b>
YDB-33E	Pressure pad for hollow rams
YRH-302	Hydraulic hollow ram
Y318-03	Cross-beam (yoke) 30t
Y318-04	Fastening material kit for 1 pair of tension bolts
Y318-33	Quick-adjust nuts
Y318-37-P	460 mm tension bolts, pair
Y318-39-P	Pair of support nuts for tension bolts
Y318-10	Crank
Y318-11	Mechanical screw

## Accessories

<b>Art. No.</b>	<b>Product name</b>
Y318-36-P	205 mm tension bolts, pair
Y318-38-P	710 mm tension bolts, pair



## Goes with

**Art. No.**

**Product name**

Y-315-4

Separator for hydraulic push/pull device

Y-315-5

Separator for hydraulic push/pull device