



Product name \*

## Universal hydraulic puller set


For removal, separation and internal extraction of particularly large and tight bearings, gears, discs, etc. in industry and commercial vehicles.

Art. No. Y58-500  
 Series YX8-X00  
 EAN 4021176870842



	Technical attribute	Metric	Imperial
	Spread	460 - 1200 mm	18 1/8 inch
	Depth	700 mm	27 5/8 inch
	Distance of side screw	235 - 540 mm	9 1/4 - 21 1/4 inch
	Depth of side screw	400 mm	11 7/8 inch
	Diameter of the shaft	75 - 330 mm	3 inch
	Inner diameter of ball bearing	75 - 230 mm	
	Maximum load as a 2-arm puller	45 t	49.6 US t
	Maximum load as a 3-arm puller	50 t	55.1 US t
	Maximum load as pulling device only with tension bolts	35 t	38.6 US t
	Maximum load as pulling device with separator	30 t	33.0 US t
	Maximum load as pulling device with internal extractor	25 t	27.5 US t



	<b>Technisches Attribut</b>	<b>Metric</b>	<b>Imperial</b>
max.	Maximum pressure	498 bar	498 bar
	Weight	335 kg	
	Number of jaws	3	3



## Technologies



### HYDRAULIC

Pullers with hydraulic function.



## Content

<b>Art. No.</b>	<b>Product name</b>
Y-521-E	Internal extractors
YHP-325	Hydraulic hand pump
Y-515-6	Separator for hydraulic push/pull device
YDB-55E	Pressure pad for hollow rams
YRH-603	Hydraulic hollow ram
Y50-180	Push/pulling device (without hydraulic hollow ram for pump drive)
Y50-206	3-jaw puller with swiveling jaws (without hydraulic hollow ram for pump drive)
Y518-08-P	865 mm tension bolts, pair
Y518-31-P	Pair of connectors for tension bolts
Y518-33	Quick-adjust nuts
Y505-20	2-jaw cross bar
Y518-10	Crank
Y518-11	Mechanical screw
Y50-216	3-jaw puller with swiveling jaws (without hydraulic hollow ram for pump drive)