



Product name *

Hydraulic push/pull device set

For separation and internal extraction of particularly large and tight bearings, gears, discs, etc. in industry and commercial vehicles.



Art. No. Y58-518
 Series YX8-X18
 EAN 4021176038891



	Technical attribute	Metric	Imperial
	Distance of side screw	235 - 540 mm	9 1/4 - 21 inch
	Depth of side screw	660 mm	26 inch
	Tension bolt depth with hydraulics below the cross-beam	400 mm	16 inch
	Diameter of the shaft	75 - 330 mm	3 inch
	Inner diameter of ball bearing	75 - 230 mm	
	Maximum load as pulling device only with tension bolts	35 t	38.6 US t
	Maximum load as pulling device with separator	30 t	33.0 US t
	Maximum load as pulling device with internal extractor	25 t	27.5 US t
max.	Maximum pressure	348 bar	348 bar
	Weight	220 kg	



Technologies



HYDRAULIC

Pullers with hydraulic function.



Content

Art. No.	Product name
Y-521-E	Internal extractors
YHP-325	Hydraulic hand pump
Y-515-6	Separator for hydraulic push/pull device
YDB-55E	Pressure pad for hollow rams
YRH-603	Hydraulic hollow ram
Y50-180	Push/pulling device (without hydraulic hollow ram for pump drive)
Y518-08-P	865 mm tension bolts, pair
Y518-31-P	Pair of connectors for tension bolts
Y518-33	Quick-adjust nuts
Y518-10	Crank
Y518-11	Mechanical screw